



DECLARATION OF PERFORMANCE

1. Unique product type identification: profiled sheets — tile-shaped profiled sheets, trapezoidal sheets
2. The intended use or uses of the construction product in accordance with applicable approved technical specifications, as intended by the manufacturer: **Fully supported metal sheet for roofing, external cladding, and internal lining.**

1) Solo profile — permitted thickness: 0.45–0.55 mm
 2) Valc profile — permitted thickness: 0.45–0.55 mm
 3) MMR Vilo — permitted thickness: 0.45–0.55 mm
 4) ERIC metal shingles — permitted thickness: 0.45–0.6 mm
 5) Weinberg metal shingles — permitted thickness: 0.45–0.6 mm
 6) MMR Luxor — permitted thickness: 0.45–0.6 mm
 7) Venezia — permitted thickness: 0.45–0.55 mm
 Zn zinc-plated coating — Class 1 — DX51D, Z275
 Polymer coating — Class 1 — S280GD/DX51D, Z275

3. Manufacturer: **AS Mārupes Metālmeistars, Ozolnieki, Stadiona iela 1, LV-3018**
4. Assessment and Verification of the Constancy of Performance (AVCP) system: **4**
5. Harmonised standard: **EN 14783:2013**
6. Declared performance characteristics

Key characteristics	Performance characteristics	Approved technical specifications
Fire reaction class:	A1	LVS EN 14783:2013
Fire resistance class	B (roof t1)	
Corrosion class	C3	

The performance characteristics of the above product fully match the declared performance characteristics.
 This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011, and the manufacturer specified above bears sole responsibility over it.