



PROFILE PLANT TECHNICAL SPECIFICATION

	line	thickness mm	width mm	length max	weight max t
	slitting line <ul style="list-style-type: none"> • steel coil slitting 	0,3 - 3	95 - 1500	coil	12
	punching line <ul style="list-style-type: none"> • mounting holes D10;D14;D16;D18;D14x20 • termo profiles (6-8 rows) 	0,3 - 3	100 – 620	coil	8
	bending line	0,3 - 6	1481	Till 12,20m	
	guillotine	0,3 - 6		till 3m	



C PROFILE STANDARD PARAMETERS

Profile	t	h	a;a1	b;b1
	mm	mm	mm	mm
C100/07	0,7	100	15	40
C100/10	1	100	15	40
C100/12	1,2	100	15	40
C100/15	1,5	100	15	40
C100/20	2	100	15	40
C100/25	2,5	100	22	40
C150/07	0,7	150	15	40
C150/10	1	150	15	40
C150/12	1,2	150	15	40
C150/15	1,5	150	15	40
C150/20	2	150	15	40
C150/25	2,5	150	22	40
C150/30	3	150	28	40
C200/07	0,7	200	15	40
C200/10	1	200	15	40
C200/12	1,2	200	15	40
C200/15	1,5	200	15	40
C200/20	2	200	15	40

C200/25	2,5	200	22	40
C200/30	3	200	28	40
C250/10	1	250	15	40
C250/12	1,2	250	15	40
C250/15	1,5	250	15	40
C250/20	2	250	15	40
C250/25	2,5	250	22	40
C250/30	3	250	28	40
C300/10	1	300	15	40
C300/12	1,2	300	15	40
C300/15	1,5	300	15	40
C300/20	2	300	15	40
C300/25	2,5	300	22	40
C300/30	3	300	28	40
C350/10	1	350	15	40
C350/12	1,2	350	15	40
C350/15	1,5	350	15	40
C350/20	2	350	15	40
C350/25	2,5	350	22	40
C350/30	3	350	28	40